



S.C. Ewing Shipping Ecologic S.R.L.

Ploiesti, Intr. Cazarmii, nr. 6, Bl. 155C, ap. 10

Prahova, ROMÂNIA

Tel/Fax: 0344/106 146, Mobil: 0727 886 038

E-mail: office@ewing.ro

Bunkeraj, ecologizare, produse petroliere

Βυνηκεηα, εκοηογίηηε, ηροδυε πεηροηερε

CONDITII TEHNICE DE CALITATE

combustibil lichid usor ECO tip 3-M

<i>CARACTERISTICI</i>	<i>PARAMETRI</i>	<i>METODE DE VERIFICARE</i>
Vascozitate: -la 50 °C, E	2.8	SR EN ISO 3104 - 96
Punct de congelare - °C min.	- 10	STAS 39 – 80
Aciditate minerala si alcalinitate	Lipsa	STAS 22 – 64
Apa - %	0.5	STAS 24/2 – 80
Sediment - % max.	0.6	STAS 116 – 71
Apa si impuritati - % max.	0.5	STAS 24/1 – 80
Cifra de cocs - %	4	SR EN ISO 6615 - 96
Cenusa - %	0.5	SR EN ISO 6245 – 95
Sulf - %	0.6	SR EN ISO 8754 - 96
Putere calorifica inferioara - kcal/kg min.	9700	STAS 5269 – 82
Densitate - 20 °C, g/cm ³ max.	0.910	SR EN ISO 3675 - 03