



S.C. Ewing Shipping Ecologic S.R.L.

Ploiesti, Intr. Cazarmii, nr. 6, Bl. 155C, ap. 10

Prahova, ROMÂNIA

Tel/Fax: 0344/106 146, Mobil: 0727 886 038

E-mail: [office@ewing.ro](mailto:office@ewing.ro)

**Bunkeraj, ecologizare, produse petroliere**

**Бункерей, екологизация, продукты нефтепродукты**

## CONDITII TEHNICE DE CALITATE

**PACURA MAX. 1% SULF**

**FT cf. ST 14 / 2003**

UTILIZARE: **DREPT COMBUSTIBIL ÎN FOCARELE UTILAJELOR SI INSTALATIILOR INDUSTRIALE**

CARACTERISTICI	CONDITII TEHNICE DE CALITATE		METODE DE ANALIZA		
	Pacura max.1% sulf		STAS	ISO	ASTM
	usoara	grea			
Vascozitate, - la 80 °C, °E, mm <sup>2</sup> /s, max. max.	8 59	15 115	117-87	3104	D 445 / 96
Densitate la 15 °C, g/cm <sup>3</sup> , max.	1,015		35-81	3675	D 1298 /85
Punct de congelare, °C, max.	25	25	39-80		D 97 / 96
Punct de inflamabilitate M., °C, min.	90	110	5489-80		D 92 /97
Aciditate minerala si alcalinitate	lipsa		22-64		D 664 /95
Apa si impuritati, %, max.	1,0	1,0	24/2-89	3733	D 95 /83
Sulf, %, max.	1,0	1,0	SRISO 8754/96	8754	D 4294 /90
Cenusa, %, max.	0,10	0,14	38-81	6245	D 482 / 95
Putere calorifica inferioara, Mj/kg min.	40,2	39,8	5269-82	-	D4809