



S.C. Ewing Shipping Ecologic S.R.L.

Ploiesti, Intr. Cazarmii, nr. 6, Bl. 155C, ap. 10

Prahova, ROMÂNIA

Tel/Fax: 0344/106 146, Mobil: 0727 886 038

E-mail: office@ewing.ro

Bunkeraj, ecologizare, produse petroliere

Βυνηκεηα? εεοηοβλναε? ηιοηηεε ηεηοηηεε

CONDITII TEHNICE DE CALITATE

PACURA USOARA

<i>CARACTERISTICI</i>		<i>Limite de admisibilitate</i>	<i>METODE DE VERIFICARE</i>
Vascozitate: -la 50 °C, cSt	max.	39	SR EN ISO 3104 - 96
Punct de congelare - °C	min. max.	-10 +5	ASTM D 97
Aciditate minerala si alcalinitate		Lipsa	STAS 22 – 64
Apa - %	max.	0.5	ASTM D 95
Sediment - %	max.	0.5	STAS 116 – 71
Inflamabilitate - °C	min.	66	ASTM D 93
Carbon rezidual - % m/m	max.	5	ASTM D 4530
Cenusa - %	max.	0.4	ASTM D 482
Sulf - %	max.	0.6	ASTM D 2622
Putere calorifica inferioara - kcal/kg	min.	9600	STAS 5269 – 82
Densitate - 20 °C, g/cm ³	max.	0.950	ASTM D 1298